Serial No.: NEW APPLICATION Attorney's Docket No.: UBS0015-US

Art Unit: Unknown

Inventor: Stephan ERNST et al.

Amendments to the Claims:

This listing of claims replaces all prior versions, and listings, of claims in this application.

Page 2

Listing of Claims:

a gastight screw conveyor (2) provided with an inlet (5) for mercury-containing residues (6), first heating means for heating admitted mercury-containing residues and causing mercury to evaporate, an outlet conduit (7) for mercury vapour-containing gas and an outlet channel (10) for mercury-free residues, the device (1) being provided with pump means (16) for applying an

1. (Original) Device (1) for removing mercury from mercury-containing residues (6), comprising

therefrom, and with a distillation column (17) provided with cooling means (18, 19) to cause

underpressure in the screw conveyor (2) and discharging mercury vapour-containing gas

condensation of mercury vapour from the mercury vapour-containing gas discharged with the

pump means (16), characterized in that the outlet conduit (7) is provided with second heating

means for heating the mercury vapour-containing gas.

2. (Original) Device (1) as claimed in claim 1, characterized in that the inlet comprises an inlet

funnel (5) provided with a gastight shut-off valve (9).

3. (Currently Amended) Device (1) as claimed in claims 1-2, claim 1 characterized in that the

first heating means are adapted to heat the admitted residues to a temperature higher than 350°C.

Serial No.: U.S.Nat'l. Phase of PCT/NL2004/000796

Attorney's Docket No.: OCT0019-US Page 3

Art Unit: Unknown

Inventor: Anthonius H. M. VERMEULEN

4. (Original) Device (1) as claimed in claim 3, characterized in that the first heating means are

adapted to heat the admitted residues to a temperature higher than 550°C.

5. (Currently Amended) Device (1) as claimed in any of the claims 1-4, claim 1 characterized in

that the outlet channel (10) for mercury-free residues comprises an outlet sluice (14)

provided with two gastight shut-off valves (12,13).

6. (Currently Amended) Device (1) as claimed in any of the claims 1.5, claim 1 characterized in

that the outlet conduit (7) comprises a dust filter (8).

7. (Currently Amended) Device (1) as claimed in any of the claims 1-6, claim 1 characterized in

that it is provided with air inlet means (21) and control means for admitting air for the purpose of

receiving therein and discharging mercury vapour.

8. (Currently Amended) Device (1) as claimed in any of the claims 1-7, claim 1 characterized in

that the pump means (16) are provided with third heating means for heating the mercury vapour-

containing gas.

9. (Currently Amended) Device (1) as claimed in claims 7-and 8, claim 7 characterized in that

Serial No.: U.S.Nat'l. Phase of PCT/NL2004/000796 Attorney's Docket No.: OCT0019-US

Art Unit: Unknown Page 4

Inventor: Anthonius H. M. VERMEULEN

the second and third heating means are adapted to maintain the temperature of the mercury vapour-containing gas at a value of at least 180°C.

10. (Currently Amended) Device (1) as claimed in any of the claims 1–9, claim 1 characterized in that the cooling means (19) are adapted to cool the mercury vapour-containing gas to a temperature at least lower than minus 30°C.

- 11. (Original) Method for removing mercury from mercury-containing residues (6) with a device (1) as claimed in claim 1, comprising the steps of
 - (i) admitting mercury-containing residues (6) into a gastight screw conveyor (2),
 - (ii) heating the admitted mercury-containing residues and causing mercury to evaporate,
- (iii) applying an underpressure in the screw conveyor (2) and discharging and heating mercury vapour-containing gas therefrom,
- (iv) causing mercury vapour to condense from the mercury vapour-containing gas discharged with the pump means (16), and
 - (v) collecting mercury in condensed state.
- 12. (Original) Method as claimed in claim 11, characterized in that the residues are heated in step (ii) to a temperature of 560°C.

Serial No.: U.S.Nat'l. Phase of PCT/NL2004/000796 Attorney's Docket No.: OCT0019-US

Art Unit: Unknown Page 5

Inventor: Anthonius H. M. VERMEULEN

13. (Currently Amended) Method as claimed in any of the claims 11-12, claim 11 characterized in that the underpressure to be applied in step (iii) amounts to 750 mbar.

14. (Currently Amended) Method as claimed in any of the claims 11-13, claim 11 characterized in that the mercury vapour-containing gas to be discharged in step (iii) is guided into a heated conduit (7) in which this gas is held at a temperature of at least 180°c.

15. (Currently Amended) Method as claimed in any of the claims 11-14, claim 11 characterized in that the mercury vapour-containing gas to be discharged in step (iv) is guided into a distillation column (17) which is at least partially cooled to a temperature of minus 38°C.

16. (Currently Amended) Method as claimed in any of the claims 11-15 claim 11, characterized in that while maintaining the underpressure to be applied in step (iii) air is admitted into the device (1) in order to entrain mercury vapour.